

PRODUCT SPECIFICATION


All-in-one LED Controller

HD-VP210S

1. System Overview

HD-VP210S is a three-in-one video processor that integrates traditional video processor, 2-way Gigabit network port output, and U-disk playback functions. It not only simplifies the construction of the on-site environment, but also improves the reliability of the product. It supports 2 channels of synchronous signal input and 1 channel of USB input, and can be used in hotels, shopping malls, conference rooms, exhibitions, studios and other occasions that require synchronous playback; in addition, the device also supports point-to-point input/output to allow the LED display to display A clearer picture.

2. Connection Diagram



3. Product Features

Input

- Supports 2 channels of HDMI, which can be switched at will;
- 1 channel USB input supports direct playback of videos and pictures in various mainstream formats in the root directory of the USB flash drive, and supports up to 1920×1080@30Hz high-definition video playback;
- Supports 2 channel HDMI audio input (choose one of two playback).

Output


- Comes standard with 2-way Gigabit network ports, which can be directly cascaded to the receiving card;
- The maximum loading capacity is 1.3 million pixels, with a maximum width support of 3840 pixels or a maximum height support of 2500 pixels;
- 1 channel TRS 3.5mm standard two-channel audio output.

Features

- Support limited transfer to complete;
- Support one-touch brightness adjustment;
- Supports locking buttons to prevent misuse of the display from causing abnormalities;
- Video signals can be switched, cropped, and zoomed arbitrarily;
- Support infrared remote control (optional).

4. Appearance Description


Front panel:



Key Description

No.	Button	Description
1	Power switch	Controls AC power input
2	RUN	Device running status indicator
	IR	Receive infrared remote control
	BRIGHT+	Brightness increases / Play the next program file in the U-disk
	BRIGHT-	Brightness decreases / Play the previous program file in the U-disk
	HDMI1	Select HDMI signal to play/Play the previous U-disk program
	HDMI2	Select HDMI signal to play/Play the next U-disk program
	USB	Select to play U disk program/Stop playing U-disk program
	SCALE	Partial/full screen switch button
	FREEZE	Freeze with one click / Video and image switching playback

Rear panel:




Input interface			
No.	Interface name	Quantity	Description
2	USB	1	USB2.0 input interface, adapted to USB3.0 U-disk can be inserted to play videos and pictures Video file formats: mp4, avi, mpg, mkv, mov, vob and rmvb; Video encoding: MPEG4 (MP4), MPEG_SD/HD, H.264 (AVI, MKV), FLV; Image file formats: jpg, jpeg, png and bmp Video resolution: maximum support 1920×1080@30Hz
	HDMI	2	HDMI input interface Interface form: HDMI-A Signal standard: HDMI1.4 backward compatible Resolution: VESA standard, ≤1920×1080p@60Hz Support audio input
4	Power supply	1	AC 100~240V, 50/60Hz

Output Interface			
No.	Interface name	Quantity	Description
1	Gigabit network port	2	Used to cascade receiving cards to transmit RGB data streams; each network port controls a range of 655,360 pixels. Support docking multi-function card
3	AUDIO OUT	1	TRS 3.5mm two-channel audio output interface Connect to audio power amplifier for high-power audio external amplifier


Control interface			
No.	Interface name	Quantity	Description
3	USB-B	1	Connect to computer for debugging equipment

* The schematic diagram of the remote control is as follows. It is optional. If you need it, please contact sales or technical support in advance.



5. Product Size

Unit: mm



Shenzhen

6. Basic Parameters

Parameter item		Parameter value
Chassis specifications		1U standard
Electrical Specifications	Power supply	AC 100~240V 50/60Hz
	Power consumption	14W
Working environment	Working temperature (°C)	-20°C~55°C
	Working humidity (RH)	20%RH~90%RH(no condensation)
Storage environment	Storage temperature (°C)	-20°C~60°C
	Storage humidity (RH)	10%RH~95%RH(no condensation)
Equipment Specifications	Size	W×H×D/482mm×44mm×240mm
	Net weight	2.4KG
Packing specifications	Packing size	W×H×D/515mm×82mm×355mm
	Packing weight	3.5KG
Packing List	HD-VP210S	1PCS
	USB Cable	1PCS
	HDMI Cable	1PCS
	Power Cable	1PCS
	Certificate	1PCS

Illustrate:

Copyright © 2026 Shenzhen Huidu Technology Co., Ltd.

Without the authorization of Shenzhen Huidu Technology Co., Ltd., no organization or individual may imitate, copy, modify or translate part or all of the contents of this specification.

Due to factors such as production batches, production processes, and functional upgrades, our company will appropriately adjust and revise relevant pictures, text descriptions, product parameters, and other related content. In the event of the above circumstances, no further notice will be given. The product pictures in the specification are for reference only. Please refer to the actual product.

The font used in this document is HarmonyOS Sans SC.